


VVER-1000
Reflooding Scenario Simulation
with MELCOR 1.8.6 Code
in Comparison
with MELCOR 1.8.3 Simulation



Jiří Duspiva

Nuclear Research Institute Řež, plc.
Nuclear Power and Safety Division
Dept. of Reactor Technology

2nd European MELCOR User Group Meeting
Prague, Czech Republic, March 1-2, 2010

Outline

- Motivation
- Comparison of used
 - Codes
 - Models
- Comparison of simulation results
- Reflooding scenario definition
- Visualization of results
- Summary, Conclusions



Motivation

- Presentation [dsp1] at 5th International QUENCH Workshop (1999) compared simulation of MELCOR 1.8.3 and ICARE2 V2-Mod2.3 simulation for reflooding scenario of VVER-1000
- Several simulations of Quench tests performed with MELCOR (1.8.5 and 1.8.6) and also with ICARE2
 - Quench-01 (M5, M6, I2), Quench-03 (M5, I2), Quench-06 (M5), Quench-07 (M6), and Quench-11 (M6)
- Interest to see progress in simulation of reflooding scenario with MELCOR code during last 10 years

[dsp1] J. Duspiva: VVER-1000 Core Quenching Analyses with MELCOR and ICARE Codes, 5th International QUENCH Workshop, Karlsruhe, October 19-21, 1999



Comparison of Codes MELCOR 1.8.3 to MELCOR 1.8.6

- MELCOR 1.8.3 was released in 1994 and MELCOR 1.8.6 in 2006
 - Version of MELCOR 1.8.6 YU_2911 used in the simulations was released in August 2009
- New model capabilities in MELCOR 1.8.6 in comparison with MELCOR 1.8.3
 - Reflooding model
 - Distinguished wetted and non-wetted surface temperature of components within individual COR cell
 - Position of quench front on surface of structures (mainly CL)
 - Distinguished supporting (core support plate) and non-supporting structures (guide tubes and control rods)
 - Core structure loading and failure modeling
 - New shroud and core former components in COR package
 - Melting of boundary HS
 - Molten pool models - in core and in lower plenum, oxidic and metallic
 - Lower head failure modeling
 - Control rod degradation improved for both SIC and B4C, and others
- Progress in computer power resulted in possibility to use significantly more detailed nodalization



Comparison of Models MELCOR 1.8.3 to MELCOR 1.8.6


Comparison of nodalization - three cases compared

Number of input objects	MELCOR 1.8.3	MELCOR 1.8.6	MELCOR 1.8.6 detailed COR
CV - total	69	129	187
CV - Cntn	5	29	29
CV - IO	30 / 3 loops	30 / 3 loops	30 / 3 loops
CV - IIO	14	24	24
CV - RPV	5	7	65
COR - Total/#Ring	60 / 5 rings	217 / 7 rings	217 / 7 rings
FL - Total	106	198	318
HS - Total	190	379	379
RN Classes	16	25	25

Figures prepared only for RPV, because this part is the most interesting for reflooding topic




Comparison of Models MELCOR 1.8.3 to MELCOR 1.8.6 (2)



Reactor Pressure Vessel Nodalization - RPV Figure, COR, CVH/FL Packages



Comparison of Models MELCOR 1.8.3 to MELCOR 1.8.6 (3)




Reactor Pressure Vessel Nodalization - COR, CVH/FL Packages



J. Duspiva

2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

Comparison of Models MELCOR 1.8.3 to MELCOR 1.8.6 (4)



Reactor Pressure Vessel Nodalization - COR, CVH/FL Packages



Comparison of Models MELCOR 1.8.3 to MELCOR 1.8.6 (5)

MELCOR 1.8.3 COR Model for VVER-1000

- PWR type
- 5 Rings
 - 4 rings with fuel and
 - 5th ring - core baffle modelled with other str.
 - Core barrel modelled as axial boundary HS
- Only 1 CV covers whole core
- Spacer grids modelled as part of cladding
- Control rods modelled as other str.
- Supporting or non-supporting feature distinguished only with parameter ISUP (input row CORZij02)
 - This option is defined for all components in axial level
- Lower plenum internals modelled as OS
- LHF - temperature criterion on outer surface
 - User model

MELCOR 1.8.6 COR Model for VVER-1000

- PWR type
- 7 Rings
 - 6 rings with fuel, but
 - 6th ring splitted into channel (FU) and bypass with SH component (core baffle)
 - 7th ring only in lower plenum
- 3 or 67 CVs cover whole core (incl. bypass)
- Spacer grids modelled as supporting structure with temperature condition of its failure
 - User defined type with options
 - Intact and debris
- Control rods modelled as NS
 - Advanced model applied
- SH component modelled with "Fixed" option
 - Available from M186 YT_1010 version
- Lower Plenum internal modelled as user defined SS
- LHF - zero dimensional model (LH has no insulation)



Reflooding Scenario Definition

Large LOCA

- **Initiating Event**

- Large break LOCA on the surge line between a hot leg of the primary circuit and the pressurizer with equivalent diameter 200 mm

- **Subsequent events**

- Loss of active emergency core cooling systems
- Loss of two of four HAs (one of them supplying water into down comer and the second one into upper plenum)

- **Interruption of accident progression**

- Restoration of one train of the high-pressure core cooling system in injection phase at the time 2200 s (system is connected into Cold Leg between MCP and RPV) - T_{CL-MAX} about 1200 K
- Successfully switched to recirculation phase at the time 2450 s (heat exchanger is operating)
- Water mass flow rate of restored HPI is about 57 kg/s in both phases
- Temperature of HPI water is 60 °C in injection and from 35 to 38 °C during recirculation

Time Table of Main Event
(MELCOR 1.8.3 Results)


<u>Event</u>	<u>Time [s]</u>
Initiating Event and SCRAM	0
Start of One Train of Containment Spray System	55
Start of HA	170
End of HA	410
Ring 2 Fuel Cladding Failure	1973
Ring 3 Fuel Cladding Failure	1982
Ring 1 Fuel Cladding Failure	2021
Start of HPI in Injection Phase	2200
Water Level on Bottom of Fuel	2420
HPI Switched to Recirculation	2450
Ring 4 Fuel Cladding Failure	2454
Water Level on Top of Fuel (End of Quenching)	2470
End of Calculation	9000

- Timing of main events slightly different between MELCOR 1.8.3 and 1.8.6 simulations
 - Start of HPI in injection phase changed to 2100 s in MELCOR 1.8.6 simulation to keep identical timing of water injection into core at 2420 s



Comparison of Results Water Levels in Core

- Different boil off phase
 - M183 - earlier starting of core uncover with slower water level falling
- Reflooding initiated at same time - boundary condition of comparison
- Water level rise
 - M183 faster swollen level
 - M183 slower collapsed level
- M6dc2 - slow rise in long term



NRI-REZ

VVER-1000 LOCA 200mm


NRI-IIBPN 8/03/97 17:44:08 MELCOR DV5



Comparison of Results Swollen Water Levels in Core (2)


(2)

- Different boil off phase
 - M183 - earlier starting of core uncoverly with slower water level falling
- Reflooding initiated at same time - boundary condition of comparison
- Water level rise
 - M183 faster swollen level
 - M183 slower collapsed level
- M6dc2 - slow rise in long term




Comparison of Results Collapsed Water Levels in Core (3)

- Different boil off phase
 - M183 - earlier starting of core uncover with slower water level falling
- Reflooding initiated at same time - boundary condition of comparison
- Water level rise
 - M183 faster swollen level
 - M183 slower collapsed level
- M6dc2 - slow rise in long term



Comparison of Results Cladding Maximum Temperature (1)

- Overall heat generation by fission and decay power identical
- Different treatment of energy transfer from COR to CV
 - Impact of version
 - Impact of nodalization (core periphery and radial heat losses)
- Difference in heat generation by oxidation
- More intensive heat up in M186 simulations is in accordance with ICARE2 [dsp1] or SCDAP/RELAP5 simulations [dsp2]




[dsp2] J. Duspiva: MELCOR1.8.5 and SCDAP/RELAP5
Codes Validation and Revision of MAAP Models;
Validation Exercises LBLOCA-M and LBLOCA-S,
Report UJV 11970-T, September 2002 (in Czech)




Comparison of Results Cladding Maximum Temperature (2)

- Water ingress into core starts at 2420 s (dot-dash vertical line)
- Very different maximum temperatures predicted
 - M3PN 1801.7 K
 - M6r3 2142.6 K
 - M6dc2 1699.2 K
- That is consequence of different oxidation before reflooding onset
 - M3PN 20.228 kg of H₂
 - M6r3 27.222 kg of H₂
 - M6dc2 12.578 kg of H₂




Comparison of Results Hydrogen Generation

- The highest hydrogen generation during reflooding predicted in M6r3 case due to significantly higher temperature at reflooding onset
- M183 without reflooding model significantly underestimated hydrogen generation
 - ICARE2 [dsp1] 80.75 kg
- Steam starvation condition indicated during beginning of reflooding
 - Short period in M183 a M6r3
 - Longer time period in M6dc2 - long time in some nodes





Comparison of Results Temperatures in Core - Ring 1

- Different nodalization in M183 and M186
 - Rings do not represent identical part of core
- Ring 1
 - M6dc2 - molten pool is not cooled down and cladding temperature in node below it is slowly rising



NRI-REZ
VVER-1000 LOCA 200mm
ii-b-03YU 8/27/09 11:09:39 MELCOR DV5




NRI-REZ
VVER-1000 LOCA 200mm
ii-b-03YU 9/21/09 15:44:06 MELCOR DV5





Comparison of Results Temperatures in Core - Ring 2

- Different nodalization in M183 and M186
 - Rings do not represent identical part of core
- Ring 2
 - M6dc2 - molten pool is not cooled down and cladding temperature in node below it is slowly rising
 - M6r3 - AxL22 collapsed at about 4500 s and debris cooled down



NRI-REZ
VVER-1000 LOCA 200mm
ii-b-03YU 8/27/09 11:09:39 MELCOR DV5




NRI-REZ
VVER-1000 LOCA 200mm
ii-b-03YU 9/21/09 15:44:06 MELCOR DV5





Comparison of Results Temperatures in Core - Ring 3

- Different nodalization in M183 and M186
 - Rings do not represent identical part of core
- Ring 3
 - M6dc2 - molten pool is not cooled down and cladding temperature in nodes below it are slowly rising, also radial relocation influences temperature evolution (change of trend from cooling to heat up)



NRI-REZ
VVER-1000 LOCA 200mm
ii-b-03YU 8/27/09 11:09:39 MELCOR DV5






NRI-REZ
VVER-1000 LOCA 200mm
ii-b-03YU 9/21/09 15:44:06 MELCOR DV5




Comparison of Results Temperatures in Core - Outermost Ring

- Different nodalization in M183 and M186
 - Rings do not represent identical part of core
- Ring 4 in M183 and Ring 6 in M186
 - M6dc2 and M6r3 - behavior influenced by radial relocation of hot debris




Comparison of Results Quench Front Position

- MELCOR with reflooding model calculates quench front position on surface of COR components - CL is the most important
 - This output not available in MELCOR 1.8.3
 - Earlier initiation of front falling in M6r3 case
 - Molten pool in M6dc2 case is not fully cooled down



VVER-1000 LOCA 200mm
ii-b-03YU 8/27/09 11:09:39 MELCOR DV5




VVER-1000 LOCA 200mm
ii-b-03YU 9/21/09 15:44:06 MELCOR DV5



M186r3 Case Results Bundle Configuration

(1)

- **Time 2420 s** - just before reflooding;
- Control rod degradation started in hot spot



J. Duspiva


2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

22

M186r3 Case Results Bundle Configuration

(2)


- Time 2520 s
- Upper part of fuel assemblies in R1 -R5 relocated



M186r3 Case Results Bundle Configuration

(3)

- Time 2570 s
- Formation of debris bed in R1 -R5 relocated



J. Duspiva


2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

24

M186r3 Case Results Bundle Configuration

(4)

- Time 2620 s
- Formation of debris bed in R1 -R5 relocated



J. Duspiva


2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

25

M186r3 Case Results Bundle Configuration

(5)

- Time 2670 s
- Water at elevation of debris bed bottom



J. Duspiva


2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

26

M186r3 Case Results Bundle Configuration

(6)

- Time 2720 s
- Cooling of debris bed started



J. Duspiva


2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

27

M186dc2 Case Results Bundle Configuration

(1)

- **Time 2420 s** - just before reflooding
- Control rod degradation started in hot spot (like in M6r3 case)



J. Duspiva


2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

28

M186dc2 Case Results Bundle Configuration

(2)

- Time 2520 s
- Fuel rod relocation did not yet start




J. Duspiva

2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

M186dc2 Case Results Bundle Configuration

(3)

- Time 2570 s
- Upper part of fuel assemblies in R1 -R5 relocated




J. Duspiva

2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

M186dc2 Case Results Bundle Configuration

(4)

- Time 2620 s
- Formation of debris bed in center, water level rise more intensive in R6




J. Duspiva

2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

M186dc2 Case Results Bundle Configuration

(5)

- Time 2670 s
- Formation of debris bed in center, water covers debris bed, void formation



J. Duspiva


2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

32

M186dc2 Case Results Bundle Configuration

(6)

- Time 2720 s
- Debris bed in center remain hot with void cavity



J. Duspiva

2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

Comparison of Results Final Bundle Configuration (2)




(2)

- Time 9000 s - end of calculation

M186r3

M186dc2

M183



J. Duspiva

2nd EMUG Meeting
Prague, Czech Republic, March 1-2, 2010

34



Summary, Conclusions

- Comparison of three simulations of reflooding scenario for VVER-1000 reactor performed
 - MELCOR 1.8.3 ([dsp1] 1999) with simple nodalization
 - MELCOR 1.8.6 with standard plant approach
 - MELCOR 1.8.6 with best practices to COR-CV-FL (very high CPU)
- Confirmation of too slow heat up rates during core uncovering in M183
 - Originally compared with SFD codes ICARE2 and SCDAP/RELAP5, M186 simulations in accordance
- Significantly higher hydrogen generation predicted in M186 in comparison with M183
 - Good agreement between both M186 simulation for total mass of H₂, but very different maximum generation rates
 - Maximum peak rate below 0.8 kg/s in M6r3 and 0.5 kg/s in M6dc2 (ICARE2 0.9 kg/s) - M6r3 generated more than 125 kg during reflooding, I2 only 30 kg



Summary, Conclusions

(2)

- First two simulations showed possibility to terminate SA progression and cool down core with only one HPI system, but
 - The most detailed simulation predicts non-cooled hot molten pool or debris bed
 - Reflood mass flow rate is only a little above $1\text{g}/(\text{s rod})$, which is understood as a minimum value for successful core reflooding if peak cladding temperature $< 2200\text{ K}$ [heh] \Rightarrow but this case was with higher CL temp.
 - Contradictory answers have to be understood as negative answer on coolability for this definition of scenario
 - At least activation of system with higher mass rate or more trains of this low mass rate system necessary
 - Testing of more nodalizations is very important, because application of the only one input model could result in wrong conclusion due to selection of inadequate one

[heh] W. Hering, Ch. Homann: Degraded core reflood: Present understanding and impact on LWRs, Nuclear Engineering and Design 237 (2007) 2315-2321



Summary, Conclusions

(3)

-
- Application of best practices for CRO-CV-FL had penalty in significantly higher CPU
 - Application of this approach seems not be necessary for all scenarios
 - Important for scenarios with counter-current flow in hot leg
 - Modelling of spacer grids as SS seems be more realistic than approach with their modelling as part of cladding
 - It enables to terminate relocation of large debris particles



End of Presentation

Thank You for Your Attention

