

pco.edge 4.2

scientific CMOS camera

high resolution

2048 x 2048 pixel

low noise

0.8 electrons



lightsheet
option

USB 3.0

Camera
Link

high dynamic range

36 000:1

high speed


100 fps

high quantum efficiency


> 70 %

features


Selectable rolling shutter operation modes of pco.edge cameras.




dual outside in



dual top down



dual inside out



single top down

rolling shutter readout modes – optimized for synchronization of microscopes and scanning applications

All pco.edge sCMOS cameras from the beginning feature a variety of precise synchronization modes, which are optimized for advanced microscopy imaging and scanning. The flexible frame and line triggers with very low latency in combination with the free selectable readout modes can easily be combined to cover every modern microscopy situation to name a few:

- lightsheet microscopy
- selective plane imaging microscopy (SPIM)
- structured illumination microscopy
- localizations microscopy (GSD, PALM, STORM, dSTORM)
- spinning disk confocal microscopy
- RESOLFT


For example, one mode is used in a lightsheet or SPIM application, the lower right rolling shutter operational mode “single top down” operation is convenient to properly synchronize the camera exposure with the scanner. On the other hand, if speed is required and a flash like exposure is applied the upper left mode “dual outside in” is used for localization microscopy techniques like GSD, PALM or STORM.

features


free of drift

The pco.edge sCMOS cameras feature temperature stabilized Peltier cooling, allowing for continuous operation free of drift phenomena in image sequences capture. This is achieved by the proper selection and sophisticated combination of electronics and FPGA algorithms.

As the measurement result shows while running at full speed of 100 frames/s over 4 hours measuring time the camera doesn't show any significant drift (figure on the right side). This degree of stability enables long-term measuring series, which should be quantitatively evaluated and processed. For example, in PCR (Polymerase Chain Reaction) applications, when so-called melting curves must be measured, the fluorescence in multi-well plates with different samples is recorded over a longer time at different sample temperatures. Here all the images are used for processing, which is only possible if the offset is stable and the camera is free of drift.



Mean dark signal drift measurement of a pco.edge camera stabilized at +5 °C over a 4 hour period recorded at 100 frames/s (1 count = 0.5 electron).



The graph shows the signal-to-noise (SNR) curves of a typical emCCD camera (gain = 1000) and a pco.edge 4.2 camera vs. number of photons.

reaching emCCD domain


In the past emCCD image sensors featuring on-chip amplification were developed to detect the lowest level of light. However, amplification, while reducing read out noise, comes at the expense of dynamic range. Both features are not possible simultaneously in emCCD sensors. In addition, the amplification process generates excess noise, which reduces the effective quantum efficiency (QE_{eff}) of the emCCD sensor by the factor of two (e.g. the 90 % QE of a back illuminated emCCD sensor has an QE_{eff} of 45 %). The excess noise present in emCCDs makes the pco.sCMOS the sensor of choice at light conditions above 1 photon per pixel (at 70 % QE, assuming a cooled sensor with dark current = 0). Furthermore, available emCCD sensors are limited in resolution and frame rate.

features

readout noise in sCMOS


The EMVA 1288 standard explains that in principle for each pixel in an image sensor the noise behavior is determined by recording many images and calculating the time dependent variation or deviation of each pixel from its mean value. This is the determination of the root mean square (rms) value for each pixel. Since the widely used CCD image sensors don't have a separate output stage for each pixel, the variation of the noise between each pixel is minimal. Therefore, instead of measuring many images, it is sufficient to measure two images, calculate the variance for each pixel and average these variances within the image to obtain an rms value for the image sensor. For CCD image sensors this simplification is a good approximation and has been now for years to describe the readout noise of image sensors in general.

However, CMOS image sensors, including scientific CMOS image sensors, feature a different behavior such that the simplified rms determination with the averaging across the whole image sensor is not sufficient to describe the noise behavior. The figure top right shows the result of time series of dark images, where for each pixel an rms value is calculated along the time axis and the results are shown in this histogram, showing the readout noise distribution for the total image sensor. Since two different pixel clocks are available in turn two curves are provided.



Noise distribution of the rms raw data values (noise filter off) of each pixel in the dark image of a pco.edge 4.2 at different readout speeds (slow scan / fast scan).

A valuable characterization of these rms value distributions is the so called median value, which is the point where 50% of all values are larger and smaller. For comparison the rms value measured by the simplified EMVA1288 approach is given. For a CCD image sensor these values would be identical, but for CMOS image sensors they start to diverge. For comparison of different cameras and image sensors both values can be used. For practical use it should be considered, that these values are calculated from a large series of recorded images.



The left figure shows the same fast scan curve of the pco.edge 4.2 only in a logarithmic y-axis (frequency) scaling, to emphasize that most of the pixels have an average readout noise in time that is smaller than 1 electron and there are few pixels (less than 1 % of the maximum), which have a readout noise of 3 – 6 electrons.


Noise distribution of the rms raw data values (noise filter off) of each pixel in the dark image of a pco.edge 4.2 at the fast readout speed. Graph is identical to figure on the top but in logarithmic y- axis scaling.

features


superior image quality

The pco.edge sCMOS camera features outstanding low read out noise. Even at maximum speed of 100 frames/s at full resolution of 2048 x 2048 pixel the noise is $1.0 e^-$ med. Moreover the pco.edge provides an excellent homogeneous pixel response to light (PRNU, photo response non-uniformity) and an excellent homogeneous dark signal pixel behaviour (DSNU, dark signal non-uniformity), which is achieved by a sophisticated electronic circuit technology and firmware algorithms.

The lower figure shows a comparison of a scientific grade CCD and the new pco.sCMOS image sensor under similar weak illumination conditions. This demonstrates the superiority of sCMOS over CCD with regards to read out noise and dynamic, without any smear (the vertical lines in the CCD image).




Dark image comparison with the measured distribution of “hot blinking” pixels at 5°C of the image sensor. The left image gives a 3D view with the sophisticated “blinker filter” algorithm off and the right image shows the result with the filter switched on.



The left image was recorded by a scientific CCD camera while the right image was recorded by a pco.edge under identical conditions.

flexibility and free of latency

User selectable choice of rolling shutter modes for exposure provides flexibility for a wide range of applications. The advantages of rolling shutter are high frame rates and low read out noise. Due to realtime transmission of the image data to the PC, there is no latency between recording and access or storage of the data.




The top image shows an extract of a typical pco.edge recording of a grey scale with a 1 : 10 000 dynamic in 20 steps. The bottom image is a plot of the grey values profile along the centered line through the top image (with gamma 2.2).

33 000:1 dynamic range

Due to the excellent low noise and the high fullwell capacity of the sCMOS image sensor an intra scene dynamic range of better than 33 000 : 1 is achieved. A unique architecture of dual column level amplifiers and dual 11 bit ADCs is designed to maximize dynamic range and to minimize read out noise simultaneously. Both ADC values are analyzed and merged into one high dynamic 16 bit value.

features



The two images show in comparison the field of view with sCMOS resolution vs. a 1.3 Mpixel resolution, courtesy of Dr. Stefan Jakobs, Dept. of NanoBiophotonics, MPI for Biophysical Chemistry

high resolution

A 4.2 Mpixel resolution in combination with a moderate chip size (18.8 mm diagonal, 6.5 μm pixel pitch) benefits microscopy applications with low magnification factor and large field of view, thereby reducing processing times and increasing throughput. The figure compares the potential of the new field of view of the pco.edge to the 1.3 Mpixel image resolution which is widely used in microscopy applications for scientific cameras.

high speed recording and data streaming

The new pco.edge offers in fast mode a frame rate of 100 frames/s (fps) at full resolution of 2048 x 2048 pixel as a full download stream to the PC. Therefore the recording time is just limited by either the amount of RAM in the PC or, in case of a RAID system, by the capacity and number of hard disks. As in many CMOS based cameras the frame rate increases significantly if smaller regions of interest (ROI) are used. The reduction of the image area works as well in favour of the frame rate of CCD sensors, but here unwanted regions still need to be read out at the expense of the total readout speed. The typical frame rate for a 1.3 Mpixel scientific CCD camera (6 e^- read out noise) is 10 fps. The new pco.edge camera provides at 1.3 Mpixel resolution (< 1.0 e^- readout noise) a frame rate of 200 fps in comparison.

technical data Camera Link

image sensor

| | |
|----------------------------|--|
| type of sensor | scientific CMOS (sCMOS) |
| image sensor | CIS2020 |
| resolution (h x v) | 2048 x 2048 active pixel |
| pixel size (h x v) | 6.5 µm x 6.5 µm |
| sensor format / diagonal | 13.3 mm x 13.3 mm / 18.8 mm |
| shutter mode | rolling shutter (RS) with free selectable readouts, lightsheet option |
| MTF | 76.9 lp/mm (theoretical) |
| fullwell capacity (typ.) | 30 000 e ⁻ |
| readout noise ¹ | 0.9 _{med} /1.4 _{rms} e ⁻ @ slow scan 1.0 _{med} /1.5 _{rms} e ⁻ @ fast scan |
| dynamic range (typ.) | 33 000 : 1 (90.4 dB) slow scan |
| quantum efficiency | > 70 % |
| spectral range | 370 nm .. 1100 nm |
| dark current (typ.) | < 0.5 e ⁻ /pixel/s @ 5 °C |
| DSNU | < 1.0 e ⁻ rms |
| PRNU | < 0.5 % |
| anti blooming factor | 1 : 10 000 |

frame rate table²

| typical examples | fast scan | slow scan |
|------------------|-----------|-----------|
| 2048 x 2048 | 100 fps | 35 fps |
| 2048 x 1024 | 200 fps | 70 fps |
| 2048 x 512 | 400 fps | 140 fps |
| 2048 x 256 | 800 fps | 281 fps |
| 2048 x 128 | 1600 fps | 562 fps |
| 1920 x 1080 | 189 fps | 66 fps |
| 1600 x 1200 | 170 fps | 60 fps |
| 1280 x 1024 | 200 fps | 70 fps |
| 640 x 480 | 426 fps | 150 fps |
| 320 x 240 | 853 fps | 300 fps |

frame rate table extended readout mode³

| typical examples | fast scan | slow scan |
|------------------|-----------|-----------|
| 2048 + 12 x 2048 | 100 fps | 35 fps |
| 2048 + 12 x 1024 | 200 fps | 70 fps |

¹ The readout noise values are given as median (med) and root mean square (rms) values, due to the different noise models, which can be used for evaluation. All values are raw data without any filtering.

² Max. fps with centered ROI.

³ Extended readout mode with 12 columns of black reference pixel.

⁴ The high dynamic signal is simultaneously converted at high and low gain by two 11 bit A/D converters and the two 11 bit values are sophisticatedly merged into one 16 bit value.

camera

| | |
|--------------------------------|---|
| frame rate | 100 fps @ 2048 x 2048 pixel, fast scan |
| exposure / shutter time | 100 µs .. 10 s |
| dynamic range A/D ⁴ | 16 bit |
| A/D conversion factor | 0.46 e ⁻ /count |
| pixel scan rate | 272.3 MHz fast scan 95.3 MHz slow scan |
| pixel data rate | 544.6 Mpixel/s 190.7 Mpixel/s |
| binning horizontal | x1, x2, x4 |
| binning vertical | x1, x2, x4 |
| region of interest (ROI) | horizontal: steps of 1 pixel vertical: steps of 1 pixels |
| non linearity | < 1 % |
| cooling method | + 5 °C stabilized, peltier with forced air (fan) / water cooling (up to 30°C ambient) |
| trigger input signals | frame trigger, sequence trigger, programmable input (SMA connectors) |
| trigger output signals | exposure, busy, line, programmable output (SMA connectors) |
| data interface | Camera Link Full (10 taps, 85 MHz) |
| time stamp | in image (1 µs resolution) |

general

| | |
|---------------------------|-------------------------------|
| power supply | 12 .. 24 VDC (+/- 10 %) |
| power consumption | 20 W max. (typ. 10 W @ 20 °C) |
| weight | 700 g |
| operating temperature | + 10 °C .. + 40 °C |
| operating humidity range | 10 % .. 80 % (non-condensing) |
| storage temperature range | - 10 °C .. + 60 °C |
| optical interface | F-mount & C-mount |
| CE / FCC certified | yes |

lightsheet
option



technical data **USB 3.0**

image sensor

| | |
|----------------------------|---|
| type of sensor | scientific CMOS (sCMOS) |
| image sensor | CIS2020 |
| resolution (h x v) | 2048 x 2048 active pixel |
| pixel size (h x v) | 6.5 µm x 6.5 µm |
| sensor format / diagonal | 13.3 mm x 13.3 mm / 18.8 mm |
| shutter mode | rolling shutter (RS) with free selectable readouts, global reset - rolling readout (GR) |
| MTF | 76.9 lp/mm (theoretical) |
| fullwell capacity (typ.) | 30 000 e ⁻ |
| readout noise ¹ | 0.8 _{med} /1.3 _{rms} e ⁻ |
| dynamic range (typ.) | 36 000 : 1 (91.1 dB) |
| quantum efficiency | > 70 % |
| spectral range | 370 nm .. 1100 nm |
| dark current (typ.) | < 0.3 e ⁻ /pixel/s @ 0 °C |
| DSNU | < 0.3 e ⁻ rms |
| PRNU | < 0.2 % |
| anti blooming factor | 1 : 10 000 |

frame rate table²

| typical examples | |
|------------------|---------|
| 2048 x 2048 | 40 fps |
| 2048 x 1024 | 80 fps |
| 2048 x 512 | 160 fps |
| 2048 x 256 | 315 fps |
| 2048 x 128 | 610 fps |
| 1920 x 1080 | 76 fps |
| 1600 x 1200 | 69 fps |
| 1280 x 1024 | 80 fps |
| 640 x 480 | 170 fps |
| 320 x 240 | 335 fps |

camera

| | |
|--------------------------------|---|
| frame rate | 40 fps @ 2048 x 2048 pixel |
| exposure / shutter time | 100 µs .. 20 s RS 30 µs .. 2 s GR |
| dynamic range A/D ³ | 16 bit |
| A/D conversion factor | 0.46 e ⁻ /count |
| pixel scan rate | 110.0 MHz |
| pixel data rate | 220.0 Mpixel/s |
| binning horizontal | x1, x2, x4 |
| binning vertical | x1, x2, x4 |
| region of interest (ROI) | horizontal: steps of 4 pixels vertical: steps of 1 pixel |
| non linearity | < 0.6 % |
| cooling method | 0 °C stabilized, peltier with forced air (fan) / water cooling (up to 30°C ambient) |
| trigger input signals | frame trigger, programmable input (SMA connectors) |
| trigger output signals | exposure, busy, line, programmable output (SMA connectors) |
| data interface | USB 3.0 |
| time stamp | in image (1 µs resolution) |

general

| | |
|---------------------------|-------------------------------|
| power supply | 12 .. 24 VDC (+/- 10 %) |
| power consumption | 21 W max. (typ. 12 W @ 20 °C) |
| weight | 930 g |
| operating temperature | + 10 °C .. + 40 °C |
| operating humidity range | 10 % .. 80 % (non-condensing) |
| storage temperature range | - 10 °C .. + 60 °C |
| optical interface | F-mount & C-mount |
| CE / FCC certified | yes |

¹ The readout noise values are given as median (med) and root mean square (rms) values, due to the different noise models, which can be used for evaluation. All values are raw data without any filtering.


² Max. fps with centered ROI.

³ The high dynamic signal is simultaneously converted at high and low gain by two 11 bit A/D converters and the two 11 bit values are sophisticatedly merged into one 16 bit value.



technical data

quantum efficiency



camera views







USB 3.0



Camera Link

dimensions

F-mount and C-mount lens changeable adapter.



All dimensions are given in millimeter.

technical data

software

Camware is provided for camera control, image acquisition and archiving of images in various file formats. PCO provides the software Camware (Windows 7, 8 and later).

A camera SDK (software development kit) including a 32 / 64 bit dynamic link library for user customization and integration on PC platforms is available for free.

For camera interface drivers and a list of supported third party software please visit www.pco.de.

options

custom made versions
(e.g. water cooling, deep cooled,...)




Water cooling unit Aquamatic II for use with pco.edge cameras.



third party integrations

software drivers



MathWorks®



VisiView®

Molecular Devices

deep cooled version

pco.edge gold


The new pco.edge gold cameras are designed to offer long exposure times and best performance data especially in terms of read out noise and intra-scene dynamic. The scientific CMOS sensor is adjustable via air cooling to -15°C and with water cooling down to -30°C . This ensures optimized dark current noise performance even during long exposure times.



deep cooled


applications

life science




A widefield (right) and a GSDIM super-resolution (left) microscopy image of tubulin fibers obtained with a pco.edge, courtesy of Leica Microsystems, Germany

physical science




A single image of fluorescence labeled protein networks in water drops in an oil phase, which moved fast. One pixel corresponds to 0.1625 μm in reality, courtesy of Prof. Dr. Sarah Köster, Institute for X-Ray Physics, Göttingen, Germany

life science




Zebrafish with two fluorescent labels, collected with a VisiScope Confocal based on the Yokogawa CSU-W1 wide head and a pco.edge camera, courtesy of Visitron Systems GmbH, Germany

life science




Neuronal network marked with a fluorophore (false color rendering) and recorded with a pco.edge.

life science



Extract of a fluorescent slide which was scanned by a pco.edge camera in a Panoramic 250 Flash scanner for digital pathology, courtesy of 3DHitech, Hungary

life science



An image of a sequence, which was recorded with a pco.edge at 400 frame/s. The maximum signal was about 100 photons, courtesy of Prof. Engstler, University of Würzburg, Germany

application areas

■ Widefield microscopy ■ Fluorescent microscopy ■ Digital pathology ■ PALM ■ STORM ■ GSDIM ■ dSTORM ■ Superresolution microscopy ■ Lightsheet microscopy ■ Selective plane imaging microscopy (SPIM) ■ Calcium imaging ■ FRET ■ FRAP ■ 3D structured illumination microscopy ■ High speed bright field ratio imaging ■ High throughput screening ■ High content screening ■ Biochip reading ■ TIRF ■ TIRF microscopy / waveguides ■ Spinning disk confocal microscopy ■ Live cell microscopy ■ 3D metrology ■ TV / broadcasting ■ Ophthalmology ■ Electro physiology ■ Lucky astronomy ■ Photovoltaic inspection

europa

PCO AG
Donaupark 11
93309 Kelheim, Germany

fon +49 (0)9441 2005 50
fax +49 (0)9441 2005 20
info@pco.de
www.pco.de

america

PCO-TECH Inc.
6930 Metroplex Drive
Romulus, Michigan 48174, USA

fon +1 (248) 276 8820
fax +1 (248) 276 8825
info@pco-tech.com
www.pco-tech.com

asia

PCO Imaging Asia Pte.
3 Temasek Ave
Centennial Tower, Level 34
Singapore, 039190

fon +65-6549-7054
fax +65-6549-7001
info@pco-imaging.de
www.pco-imaging.de